

Certificate of Compliance

Certificate Number:
UL-US-L474828-08271-
11605102-0

Report Reference:
E474828-20150611

Issue Date:
2025-02-24

Issued to:

BIMED TEKNIK ALETLER SAN TIC A S
Deliklikaya Mah. Yuzbasi Mehmet Hilmi Cad. No:28 Ic Kapı No:1,
Arnavutkoy, ISTANBUL, 34555, TR

This certificate confirms that representative samples of:

CYMJ - Cable Fittings for Use in Zone Classified Hazardous Locations

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

UL 50E, Enclosures for Electrical Equipment, Environmental Considerations - Edition 1 - Revision Date 2012/04/27

UL 514B, Conduit, Tubing, and Cable Fittings- Edition 6 - Revision Date 2014/11/21

UL 2225, 4th Ed., Rev. 2016-01-29, Cables and Cable-Fittings for Use in Hazardous

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L474828-08271-11605102-0
Report reference E474828-20150611
Date 2025-02-24

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
Series Orion , KBA, followed by 1 thru 10, may be followed by S, XS, XM or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC, TC-ER and TC-ER-HL cable, thread sizes 1/2 to 3-1/2 in. NPT or M20 to M110
Series Orion , KBA, followed by 1 thru 10, may be followed by S, XS, XM or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC, TC-ER and TC-ER-HL cable, thread sizes 1/2 to 3-1/2 in. NPT or M20 to M110
Series Orion Lower Temperature (Orion LT) , KBA, followed by 1 thru 3, may be followed by X, followed by M or N, followed by LT, followed by B, BN, X, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC-ER-HL cable, thread sizes 1/2 to 1 in. NPT or M20 to M32
Series Orion Lower Temperature (Orion LT) , KBA, followed by 1 thru 3, may be followed by X, followed by M or N, followed by LT, followed by B, BN, X, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC, TC-ER and TC-ER-HL cable, thread sizes 1/2 to 1 in. NPT or M20 to M32
Series Orion Lower Temperature (Orion LT) , KBA, followed by 1 thru 3, may be followed by X, followed by M or N, followed by LT, followed by B, BN, X, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC, TC-ER and TC-ER-HL cable, thread sizes 1/2 to 1 in. NPT or M20 to M32
Series Orion , KBA, followed by 1 thru 5, may be followed by S, XS, XM or L, followed by M or N, followed by B, BN, X, or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC-ER-HL cable, thread sizes 1/2 to 1-1/2 in. NPT or M20 to M50
Series Taurus , KBAT, followed by 1 thru 5, may be followed by S or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC-ER-HL cable, thread sizes 1/2 to 1-1/4 in. NPT or M20 to M40
Series Taurus , KBAT, followed by 1 thru 6, may be followed by S or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC, TC-ER and TC-ER-HL cable, thread sizes 1/2 to 2 in. NPT or M20 to M63
Series Taurus , KBAT, followed by 1 thru 6, may be followed by S or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC, TC-ER and TC-ER-HL cable, thread sizes 1/2 to 2 in. NPT or M20 to M63
Series Orion Universal , KBAU, followed by 1 thru 10, may be followed by S, XS, XM or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC, TC-ER and TC-ER-HL cable, thread sizes 1/2 to 3-1/2 in. NPT or M20 to M110
Series Orion Universal , KBAU, followed by 1 thru 10, may be followed by S, XS, XM or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC, TC-ER and TC-ER-HL cable, thread sizes 1/2 to 3-1/2 in. NPT or M20 to M110

CERTIFICATE OF COMPLIANCE

Certificate number UL-US-L474828-08271-11605102-0
Report reference E474828-20150611
Date 2025-02-24

Series Orion Universal , KBAU, followed by numerals 1 thru 5, may be followed by S, XS, XM or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC-ER-HL cable, thread sizes 1/2 to 1-1/2 in. NPT or M20 to M50
---	---

Certificate of Compliance

Issued to:

BIMED TEKNIK ALETLER SAN TIC A S
Deliklikaya Mah. Yuzbasi Mehmet Hilmi Cad. No:28 Ic Kapı No:1,
Arnavutkoy, ISTANBUL, 34555, TR

This certificate confirms that representative samples of:

CYMJ7 - Cable Fittings for Use in Zone Classified Hazardous Locations Certified for Canada

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

CSA-C22.2 No. 18.3-12, Conduit, Tubing, and Cable Fittings - Edition 2

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L474828-08291-11605102-0
Report reference E474828-20150611
Date 2025-02-24

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model	Product Description
Series Orion , KBA, followed by 1 thru 10, may be followed by S, XS, XM or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC, TC-ER and TC-ER-HL cable, thread sizes 1/2 to 3-1/2 in. NPT or M20 to M110
Series Orion Lower Temperature (Orion LT) , KBA, followed by 1 thru 3, may be followed by X, followed by M or N, followed by LT, followed by B, BN, X, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC-ER-HL cable, thread sizes 1/2 to 1 in. NPT or M20 to M32
Series Orion Lower Temperature (Orion LT) , KBA, followed by 1 thru 3, may be followed by X, followed by M or N, followed by LT, followed by B, BN, X, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC, TC-ER and TC-ER-HL cable, thread sizes 1/2 to 1 in. NPT or M20 to M32
Series Orion Lower Temperature (Orion LT) , KBA, followed by 1 thru 3, may be followed by X, followed by M or N, followed by LT, followed by B, BN, X, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC-ER-HL cable, thread sizes 1/2 to 1 in. NPT or M20 to M32
Series Orion , KBA, followed by 1 thru 5, may be followed by S, XS, XM or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC-ER-HL cable, thread sizes 1/2 to 1-1/2 in. NPT or M20 to M50
Series Orion , KBA, followed by 1 thru 5, may be followed by S, XS, XM or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC-ER-HL cable, thread sizes 1/2 to 1-1/2 in. NPT or M20 to M50
Series Taurus , KBAT, followed by 1 thru 5, may be followed by S or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC-ER-HL cable, thread sizes 1/2 to 1-1/4 in. NPT or M20 to M40
Series Taurus , KBAT, followed by 1 thru 5, may be followed by S or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC-ER-HL cable, thread sizes 1/2 to 1-1/4 in. NPT or M20 to M40
Series Taurus , KBAT, followed by 1 thru 6, may be followed by S or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC, TC-ER and TC-ER-HL cable, thread sizes 1/2 to 2 in. NPT or M20 to M63
Series Orion Universal , KBAU, followed by 1 thru 10, may be followed by S, XS, XM or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC, TC-ER and TC-ER-HL cable, thread sizes 1/2 to 3-1/2 in. NPT or M20 to M110
Series Orion Universal , KBAU, followed by 1 thru 5, may be followed by S, XS, XM or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC-ER-HL cable, thread sizes 1/2 to 1-1/2 in. NPT or M20 to M50

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

CERTIFICATE OF COMPLIANCE

Certificate number UL-CA-L474828-08291-11605102-0
Report reference E474828-20150611
Date 2025-02-24

Series Orion Universal , KBAU, followed by 1 thru 5, may be followed by S, XS, XM or L, followed by M or N, followed by B, BN, X or A, followed by C or S, may be followed by -WC or -WS.	Cable Fittings, for use only with TC-ER-HL cable, thread sizes 1/2 to 1-1/2 in. NPT or M20 to M50
--	---